



Single Turret



Italian Leader Worldwide

EUROMAC
SLITTERS REWINDERS

Euromac Costruzioni Meccaniche S.r.l. - Strada Statale 31 n.6 - 15030 Villanova Monf. - Italia
TEL. +39 0142.483195 - FAX +39 0142.483611 - www.euromacslitters.com • euromac@euromacslitters.com



TB-3T1 Single Turret

UNWIND - Separate shaftless or shafted unwind stand • Dancing roller for tension control • Pneumatic brake or electric motor • Automatic webguiding system.

SLITTING - Slitting system at shear-cut rotary blades or with oscillating razorblades • Knifeholders on shaft or linear bearing guides • Specific web path for Wrap-cut or Tangent-cut • Manual, semi-automatic or full-automatic positioning of slitting blades • Driven spreader roller(s) for separation of slitted stripes.

WEB PATH - Overhead web path or footboard • Aluminum idler rollers • Driven main pull roll with own pressure roller or "S" wrap.

REWIND - Single Turreted centre wind, assisted by lay-on rolls • Automatic cycle for downtimes of aprox. 30 seconds • Transversal splice with automatic sequence • Air expanding rewind shafts and lay-on unit control • Roll offloading by manual or motorised trolley.

AUTOMATION - PLC for all machine functions and controls • Touch screen digital operator panel • Modem for remote monitoring.



MAIN SPECIFICATION	Standard	Option
Maximum web widths	1.000 to 2.000 mm	(or Custom)
Maximum rewind diameter	600 to 1.000 mm	(or Custom)
Maximum unwind diameter	800 to 1.800 mm	(or Custom)
Webguide stroke	± 75 mm	(or Custom)
Core diameter	76, 152 mm	(or Custom)
Maximum working speed	500-1000 m/min	(or Custom)
Web tension range	Customised	
Rewind system	Centre and Lay-on rolls	(Gap rewind)
Slitting	Oscillating razors	(Shear)
Material	Paper, Metalised paper, Paper laminates, Paper/PE, Alufoil, Alufoil laminates, Laminates, Coextrusion films.	
Best Choice for	Aluminum+Paper, Metalised Paper	